



### USB To Serial Adapter Cable

- Fully compliant with USB 1.1 specifications
- Full-Duplex Transmitter and Receiver (TXD and RXD)
- Six Modem Control Pins (RTS, CTS, DTR, DSR, DCD, and RI)
- Parity Error, Frame Error, and Serial Break Detection
- Supports baud rates from 1.2 - 115.6 K
- Requires Windows<sup>®</sup> 98, ME<sup>®</sup>, 2000, XP, Vista or Windows 7

## Specifications: USB To Serial Adapter Cable

### Cable Specifications:

<b>Conductor (Qty. 1 Twisted Pair):</b>		<b>Overall Cable:</b>	
Conductor Type:	28AWG (7/0.12) Tinned Copper	Foil Shield:	Aluminum Mylar 100% Coverage
Insulation:	HD-PE O.D. 0.85 ± 0.05mm	Braided Shield:	16/4/0.10 Tinned Copper 65% Coverage
Colors:	(white, green)	Jacket:	PVC Translucent White O.D. 4.5 ± 0.10mm
<b>Conductor (Qty. 2):</b>			
Conductor Type:	24AWG (7/0.20) Tinned Copper		
Insulation:	SR-PVC O.D. 1.15 ± 0.05mm		
Colors:	black, red		

### Connector Specifications:

<b>USB Connector:</b>		<b>DB9 Connector:</b>	
Connector Type:	USB A Male	Connector Type:	DB9 Male
Contact Material:	Brass 3µm Gold Plating	Contact Material:	Brass 3µm Gold Plating
Insulation:	White PBT	Insulation:	White PBT

### Physical Characteristics:

Cable Length:	5ft
USB Connector:	USB Type A Male
Serial Port Connector:	DB9 Male
Serial Housing Dimensions:	17.0 x 33.0 x 55.5mm
Weight:	0.15lb

Item Number	Description	Weight (lb)
26887	USB to DB9 Serial Adapter Cable	0.15