

# Specifications

## DSP Modes (Presets)

Speech/Flat

## Cartridge Type

Electret Condenser (16 mm)

## Polar Pattern

Unidirectional (Cardioid)

## Bit Depth

16-bit/24-bit

## Sampling Rate

48 kHz

## Frequency Response

20 Hz to 20,000 Hz

## Adjustable Gain Range

0 to +36 dB

## Sensitivity

-40 dBFS/Pa at 1 kHz <sup>[1][2]</sup>

## Maximum SPL

130 dB SPL <sup>[2]</sup>

## Headphone Output

3.5 mm (1/8")

## Power Requirements

Powered through USB connector

## Mute Switch Attenuation

Yes

## Mounting Stand

Included

## Stand Adapter

1/4 inch 20 thread (standard tri-pod mount)

## Housing

PC/ABS

## Net Weight

Without Mounting Stand
0 . 09 kg (3 . 17 oz. )
With Mounting Stand
0 . 16 kg (5 . 64 oz. )

## Dimensions

66 x 67 x 65 mm H x W x D

## Dimensions with Stand


89 x 142 x 97 mm H x W x D

## Cable

1 m USB-A cable/1 m USB-C cable

[1] Pa=94 dB SPL [1] Pa=94 dB SPL [1] Pa=94 dB SPL

[2]At Minimum Gain, Flat Mode [2]At Minimum Gain, Flat Mode



Polar Pattern

